

Sub A

1
2

>

Abstract

3 A novel cover for a spectator at a sporting or other outdoor
4 event having a generally tubular or cylindrical shape open at
5 one end and closed at the other end having an approximate twenty
6 inch diameter and a axial length of about forty-five inches when
7 finished. The lower portion of the cylinder is formed of a
8 multi-layer material with a waterproof base of about twenty
9 inches in diameter and eight inches in axial length when
10 finished. The waterproof base has an inner insulated layer.
11 The outer layer may be of vinyl or plastic and the inner layer
12 may be wool, cotton, or any other insulating material.

13 The upper portion of the bag is formed of a wind and water
14 resistant material such a dense or tightly woven nylon material
15 for an outer layer and double sided fleece material formed of
16 wool, cotton, or other suitable fabric which is both soft and
17 flexible.

18 The upper portion of the bag is kept open along the major part
19 of its axial length to permit the user easy entry to the bag.

20 Along the axial portion of the bag on either side of the opening
21 are mating hook and loop fastening material (although a zipper
22 could be substituted for the hook and loop closure.

23 At the other end of the bag, away from the base is formed,
24 usually by sewing, a runway through which runs a cord formed of
25 polyester or nylon. The cord exits the runway either at the end
thereof or through eyelits formed in the outer surface of the

1 runway at either end thereof. The cord has a "barrel stop" or
2 similar termination to prevent the cord from sliding into the
3 stitched runway.

4 A plurality of pockets are attached to the bag. One pocket is
5 inside the bag at the upper or waist level and the other on the
6 outside of the bag at a level between one-third to one-quarter
7 the distance from the base of the bag. Either or both pockets
8 may be closed by either a mating hook and loop closure or any
9 other suitable closing structure.

10 The entire bag is able to be fitted in a carry bag, cylindrical
11 in shape, with a rimmed top for a two cord shoulder strap which
12 acts as a closure for the carry bag. A clasp is attached to the
13 carry bag to enable its attachment to the bag while the bag is
14 itself in use.